

Forklift Seat Belts

Seat Belts for Forklift - Explained in the Regulation guidelines are the use of operative restraints and seatbelts on lift trucks. It states that the responsibility falls on the employers' to make sure that every machine, piece of equipment and device is utilized properly utilized in accordance to the instructions of the maker.

Regarding their inspection, fabrication, use, design and maintenance Rough Terrain lift trucks have to meet the guidelines of ANSI Standard ASME B56.6-1992.

Mobile equipment such as side boom tractors along with a Rollover Protective Structure (ROPS), ought to contain seat belts which meet the Society of Automotive Engineers safety requirements; Society of Automotive Engineers Standard J386 JUN93, Operator Restraint System for Off-Road Work Machines. If whatever mobile machinery includes seat belts required by law, the operator and subsequent passengers have to ensure they utilize the belts every time the motor vehicle is in motion or engaged in operation in view of the fact that this could cause the equipment to become unbalanced and thus, unsafe.

When a seat belt or different driver restraint is required on a lift truck.

The seat belt requirements while operating a forklift depend on various factors. Whether or not the lift truck is outfitted along with a Rollover Protective Structure, the kind of lift truck itself and the year the forklift was manufactured all add to this determination. The manufacturer's directions and the requirements of the applicable standard are referenced in the Regulation.

In the case of powered industrial trucks, ANSI Standard ASME B56.1-1993 refers to an operator restraint device, enclosure or system. A driver restraint device, enclosure or system is designed so as to help the driver in lowering the chance of entrapment of the head and/or torso between the truck and the ground in the event of a tip over. The system or restraint device might comprise a seat belt, while a seat belt is not necessarily a part of such device or system.